



národní
úložiště
šedé
literatury

Thin Film Composite Membrane for Effective Raw Biogas Upgrading to Pipeline Quality Methane

Kárászová, Magda
2012

Dostupný z <http://www.nusl.cz/ntk/nusl-126626>

Dílo je chráněno podle autorského zákona č. 121/2000 Sb.

Tento dokument byl stažen z Národního úložiště šedé literatury (NUŠL).

Datum stažení: 25.04.2024

Další dokumenty můžete najít prostřednictvím vyhledávacího rozhraní nusl.cz .

Thin film composite membrane for effective raw biogas upgrading to pipeline quality methane

M. Kárászová, J. Vejrazka, V. Veselý, ¹K. Friess, ¹A. Randová, ²J. C. Jansen, P. Izák
Institute of Chemical Process Fundamentals of the AS CR, Rozvojova 135, 165 02, Prague 6,
Czech Republic; Tel.: +420-220390204, E-mail: izak@icpf.cas.cz; ²Institute of Chemical
Technology in Prague, Technická 5, 160 00, Prague 6, Czech Republic; ³Institute on
Membrane Technology, ITM-CNR, c/o University of Calabria, Via P. Bucci 17/C, 87030
Rende (CS), Italy.

It is generally accepted that world's main resources of fossil fuels will be depleted during the oncoming decades. Looking for adequate alternatives of new and renewable sources of energy is one of most important tasks of contemporary science [1]. Nowadays "western civilization" depends strongly on the use of fossil fuels although their mining and production are increasingly expensive. In addition, significant increase of air pollution with different carbon containing substances like aromatic hydrocarbons or carbon black takes place. One of the possible alternatives is intensive exploitation of biogas, a "dormant" byproduct of some industrial and agricultural processes today. Besides the varying CH₄/CO₂ ratio, the humidity and corrosive gases present in biogas still constitute a major problem for biogas industrial utilization (fuel for cars or pipeline). Therefore, the most feasible way of converting the chemical energy stored in biogas to heat or electricity is now still combustion. The combined heat and power plants are usually connected directly to the biogas sources like sewerage plants [2], landfills and farms.

In this contribution we propose a method to upgrade biogas to the same quality of fuel standard natural gas. The latter contains more than 95 vol. % of methane. Using traditional membranes, such concentration of methane in the retentate could only be achieved using a multistep process. A recently proposed method for raw biogas purification from impurities and carbon dioxide by condensing water on swollen thin film composite membranes was found to be highly effective [3]. The hydrophilic reverse osmosis membrane promotes the formation of a very thin selective water layer under condensing conditions below the dew point of the raw biogas feed. The large difference in permeability of the impurities in raw biogas (carbon dioxide, hydrogen sulfide) and methane through the water layer enables upgrading of raw biogas to biomethane quality in a single stage. Contrary to the classical purification processes, the proposed method does not require any biogas pretreatment, which makes this approach economically attractive. It represents an innovative approach to production of biomethane from biogas.

References

1. R. Dewil, L. Apples, Energy Use of Biogas Hampered by the Presence of Siloxanes, *Energ. Convers. Manage.* 47 **2006** 1711-1722.
2. W. Xiao, W. Yao, Z. Jun, C. Miller, Biogas and CH₄ Productivity by Co-digesting Swine Manure with Three Crop Residue as an External Carbon Source, *Bioresour. Technol.*, 101 **2010** 4042-4047.
3. M. Poloncarzová, J. Vejrazka, V. Veselý, P. Izák, Effective purification of biogas by "condensing liquid membrane", *Angewandte Chemie Int. Ed.*, 50 **2011** 669-671.

Acknowledgement:

This research was supported by grant No. P106/10/1194 from Czech Science Foundation.