



národní
úložiště
šedé
literatury

Organic Vapour Sorption and Permeation in Polymer Gel Membrane Containing Imidazolium Based Ionic Liquid

Morávková, Lenka
2014

Dostupný z <http://www.nusl.cz/ntk/nusl-175015>

Dílo je chráněno podle autorského zákona č. 121/2000 Sb.

Tento dokument byl stažen z Národního úložiště šedé literatury (NUŠL).

Datum stažení: 19.04.2024

Další dokumenty můžete najít prostřednictvím vyhledávacího rozhraní nusl.cz .

Organic vapour sorption and permeation in polymer gel membrane containing imidazolium based ionic liquid

L. Morávková, ¹O. Vopička, J. Vejražka, H. Vychodilová, Z. Sedláková, ¹K. Friess, P. Izák
Institute of Chemical Process Fundamentals of the AS CR, Rozvojová 135, 16502 Prague 6,
Czech Republic; tel. +420220390133, e-mail: sedlakova@icpf.cas.cz; ¹Dep. of Physical
Chemistry, Institute of Chemical Technology, Technická 5, 16628 Prague 6, Czech Republic.

The volatile organic compound (VOC) emissions mean an air pollution as well as energy and economic losses [1,2,3]. In order to capture the VOC substances, several conventional methods such as absorption, adsorption, condensation, etc. [4] might be used. On the contrary, relatively new membrane technologies based on vapour permeation have attracted attention as an alternative with the potential advantages of low operating cost, simple and compact equipment, easy operation requiring no regeneration steps, and energy efficiency [2,4,5]. Recently, membranes based on an ionic liquid have been focused as a new kind of membranes because of ionic liquids negligible volatility and their possibility to improve the transport properties [6,7].

In this work, vapour sorption and transport properties were studied for the aliphatic hydrocarbon (hexane), branched hydrocarbon (isooctane), and alcohol (ethanol) using a gravimetric sorption apparatus [8,9] and a “home-made” laboratory-scale apparatus [10], respectively. The ionic liquid polymer gel membrane based on poly(vinylidene fluoride-co-hexafluoropropylene) (abbreviated p(VDF-HFP)) was prepared by solvent casting from a solution in acetone [11]. The used membrane contains 80 wt. % of the imidazolium based ionic liquid 1-ethyl-3-methylimidazolium bis(trifluoromethylsulfonyl)imide ([emim][Tf₂N]).

Both vapour sorption and permeation were negligible in the virgin p(VDF-HFP) whereas the sorption and transport properties were improved by the presence of the ionic liquid [emim][Tf₂N] in the membrane. The vapour sorption and permeation of n-hexane and isooctane are significantly lower than that of ethanol. The potential applicability of the ionic liquid contains membrane for organic vapour removal from air is confirmed by its organophilic character.

Acknowledgements: The financial support from the Technology Agency of the Czech Republic (project TE01020080), MŠMT (project LD-13018) and the Czech Science Foundation (project 14-12695S) are greatly appreciated.

References

1. K. Zhao et al. *Environ. Technol.* 32 (2011) 617–623.
2. L. Liu et al. *Canad. J. Chem. Eng.* 87 (2009) 456–465.
3. M. Bodzek, *Pol. J. Environ. Studies* 9 (2000), 1–12.
4. G. Rebollar-Perez et al. *Membranes* 1 (2011) 80–90.
5. P. Bernardo et al., *Ind. Eng. Chem. Res.* 48 (2009) 4638–4663.
6. P. Bernardo et al., *Sep. Purif. Technol.* 97 (2012) 73–82.
7. K. Friess et al., *J. Membr. Sci.* 415–416 (2012) 801–809.
8. O. Vopička et al., *J. Membr. Sci.* 330 (2009) 51–56.
9. O. Vopička et al., *Chemické listy* 103 (2009) 310–314.
10. J. C. Jansen et al., *Macromolecules* 44 (2011) 39–45.
11. L. Morávková et al., *Chem. Pap.*, submitted.