



národní
úložiště
šedé
literatury

Granular Dynamics of the Mixing Processes for Different RPM Using DEM

Jirounková, K.
2014

Dostupný z <http://www.nusl.cz/ntk/nusl-175022>

Dílo je chráněno podle autorského zákona č. 121/2000 Sb.

Tento dokument byl stažen z Národního úložiště šedé literatury (NUŠL).

Datum stažení: 05.07.2024

Další dokumenty můžete najít prostřednictvím vyhledávacího rozhraní [nusl.cz](http://www.nusl.cz) .

Granular dynamics of the mixing processes for different RPM using DEM

¹K. Jirouňková, ^{1,2}J. Havlica, ³M. Kohout

¹ University of Jan Evangelista Purkinje, České mládeže 8, Ústí nad Labem, 400 96, Czech Republic

² Institute of Chemical Process Fundamentals of the ASCR, v. v. i.; Rozvojová 2/135, 165 02 Prague, Czech Republic; tel. +420 220 390 251, e-mail: havlica@icpf.cas.cz

³ Institute of Chemical Technology, Technická 5, 166 28 Prague, Czech Republic

The granular materials are usually assemblies of complex bodies varying in size, shape and surface properties. It is often extremely complicated to handle since granular materials reveal very different behaviour under different circumstances, there is therefore need to understand how the granular layer behaves when mixing.

This paper emphasizes on the computer simulations of the granular materials via Discrete Element Method (DEM) by using open-source software LIGGGHTS. The examined process was mixing of two granular materials distinct by colour. The different initial conditions have led to finding the best way of homogenization, but it also shows the new perspective of noticing the process as a system of inseparable processes linked to each other.

Unlike the continuous simulations this method neglect the interstitial fluid, it helps to simulate motion of each particle and can be described by the second Newton law, where a sum of all forces affecting the particle consists of the pairwise contact force and the external forces. In this case the only gravitation is assumed as the external force.

In this contribution effect of different RPMs were examined. The different behaviour of granular system comes out with varying initial conditions. The behaviour of the concentrational and flow patterns dependent on the frequency of RPM was observed. It helps us to understand the process of homogenization valued by the Lacey and Poole mixing indices.

Acknowledgements: This work was supported by the grant GACR P105/12/0664 from the Czech Science Foundation.