

TONITE – SUPPORTED NANOSCALE AMORPHOUS Fe–Ti HYDROUS OXIDES FOR OXIDATIVE/ADSORPTIVE REMOVAL OF ARSENITE AND ARSENATE FROM WATER

Dong Nguyen Thanh^{1*}, Zdeněk Bašný², David Kubíčka¹,
Lucie Kolerová¹, Karla Černá¹

¹search Institute of Inorganic Chemistry, RENTECH-UniCRe, Chempark Litvňov, Záhřež – Litvňov, 436 70, Czech Republic
²ronovský Institute of Physical Chemistry, Academy of Science of the Czech Republic, Dolejškova 3, CZ-182 23 Prague 8, Czech Republic

Toxic levels of anionic arsenic species can significantly affect drinking water supply in many areas all over the world (more than 150 million people). The World Health Organization (WHO) has recommended maximum contaminant levels of arsenic $0 \mu\text{g/L}$. Therefore, developing economical, effective and reliable treatment techniques for arsenic removal from groundwater is critical and has gained considerable attention in recent years. It has been demonstrated that the mixed oxides are more active single oxides thanks to the synergistic effects between the metals in heterogeneous oxides. Therefore, the incorporation of iron, titanium (FeTi) into adsorbent recently improved their adsorption capacity toward arsenic because they have a selective selectivity for polyoxy anions. However, separation of As-bearing fine particles treated water presented a challenge. In this research, a natural bentonite (B) was mixed with Fe–Ti hydroxide oxides (BFT) to enhance its arsenic removal capacity and adsorption property. The results indicated that the BFT adsorbent performed excellently moving both As(III) and As(V) from water. The maximum adsorption capacities for As(III) and As(V) calculated from Langmuir model are 79.2 and 54.3 mg/g , respectively. In addition, arsenite is partially converted to arsenate in the adsorption process. The amorphous hydroxide is thus a promising adsorbent for both As(III) and As(V) removal because of its excellent performance and simple low-cost synthesis.

³World Health Organization for drinking water quality. World Health Organization: Geneva, 2011.
⁴Journal of Hazardous Materials, 142 (1–3), 1–83.
⁵Journal of Hazardous Materials, 142 (1–3), 1–83.
⁶Journal of Hazardous Materials, 142 (1–3), 1–83.
⁷Journal of Hazardous Materials, 142 (1–3), 1–83.

HDS ACTIVITY OF NiMo CATALYSTS OVER Ce/Al MIXED OXIDES PREPARED MECHANOCHEMICALLY

Květa Jiráťová¹, Alla Spozhakina², Luděk Kaluža¹, Radoslína Palchevová², Jana Balabánová¹, Georgij Tyuliev²

¹Institute of Chemical Process Fundamentals of the Academy of Sciences of the Czech Republic, v.v.i., 165 02 Prague 6, Czech Republic, jiratova@icpf.cas.cz;
kaluzad@icpf.cas.cz

²Institute of Catalysis, Bulgarian Academy of Sciences, G. Bonchev str., bldg. 11, 1113 Sofia, Bulgaria, radost@ic.bas.bg; mariamaleva@yahoo.ie; tyuliev@gmail.com

The necessity of the development of hydrotreating catalysts with significantly better properties exists in the view of the strongest regulations on the contents of sulfur compounds in the transport fuels. New, so called deep hydrodesulfurization processes are necessary to achieve sulfur content in petrol close to zero. The choice of suitable, more effective support becomes other important alternative how to increase activity of HDS catalysts [1]. In this study, NiMo catalysts were synthesized by impregnation of the $\text{Al}_2\text{O}_3\text{-CeO}_2$ supports (with the quantities of CeO_2 in the range of 1–10 wt. %) prepared mechanochemically by milling of Al and/or Ce nitrates with NH_4HCO_3 . Heteropolymolybdate $(\text{NH}_4)_4\text{NiMo}_6\text{O}_{24}$ was applied as the precursor of active components Ni and Mo in catalysts for hydrodesulfurization of 1-benzothiophene (BT). Chemical analysis, BET, IR and Raman spectra, XPS were used for physicochemical characterization of the catalysts. Activity of catalysts exceeds significantly that of the reference NiMo/Al₂O₃ catalyst prepared by impregnation of classical alumina using the same precursor and having the NiMo composition (Table 1). The highest Ni synergistic effect was observed at the Ni/Mo ratio about 0.20 on the NiMo/Al₂O₃ catalytic surface.

Table 1
HDS activity at 360 °C and 1.6 MPa

Catalyst	Ce _{cat} / %	k _{cat} / mmol _{cat} / h ⁻¹ / m ² ·h ⁻¹	k _{ref} / mmol _{ref} / h ⁻¹ / m ² ·h ⁻¹
NiMo/Al ₂ O ₃	0.01	768	2.9
NiMo/Al ₂ O ₃ -1Ce	0.72	678	3.1
NiMo/Al ₂ O ₃ -2Ce	1.90	614	2.6
NiMo/Al ₂ O ₃ -4Ce	3.90	607	3.4
NiMo/Al ₂ O ₃ -10Ce	9.50	566	3.6
NiMo/CeO ₂	67.5	15	0.3
Ref. NiMo catalyst	0	434	-

Presence of cerium increased Mo content on the surface of NiMo catalysts significantly, whereas Ni content does not change practically. Specific catalyst activity was increasing with increasing Ce content in the mixed NiMo/Al₂O₃-Ce catalysts.

References

- 1) Breysser, M.; Altmshäuser, P.; Reinold, C.; Vrinat, M. Catal. Today 2003, 86, 5–16.

Acknowledgements

The authors highly acknowledge the Bulgarian and Czech Academies for Support of Scientific Cooperation, L.K. particularly appreciates and acknowledges the financial support of the Grant Agency of the Czech Republic (Grant No. P106/11/0902).