



národní
úložiště
šedé
literatury

Porosity and Cell Size of CO₂ Blown Polystyrene Foams: Experiments and Modelling.

Sovová, Helena
2016

Dostupný z <http://www.nusl.cz/ntk/nusl-254047>

Dílo je chráněno podle autorského zákona č. 121/2000 Sb.

Tento dokument byl stažen z Národního úložiště šedé literatury (NUŠL).

Datum stažení: 25.04.2024

Další dokumenty můžete najít prostřednictvím vyhledávacího rozhraní [nusl.cz](http://www.nusl.cz) .

Porosity and cell size of CO₂ blown polystyrene foams: experiments and modelling

H. Sovová,¹ A. Nistor, M. Topiař, ¹J. Kosek

Institute of Chemical Process Fundamentals of the CAS, Rozvojová 135, 16502 Prague 6, Czech Republic, tel. +420 220390234, e-mail: Sovova@icpf.cas.cz; ¹University of Chemistry and Technology Prague, Dept. of Chemical Engineering, Technická 5, 16628 Prague 6, Czech Republic, e-mail: juraj.kosek@vscht.cz.

Polymer foaming with CO₂ is a promising area of research with applications already commercialized and more on the horizon. In batch experiments, polymer absorbs supercritical CO₂ at the temperature adjusted above its glass transition temperature, T_g, until saturation is reached. Rapid depressurization is then applied, causing gas supersaturation and allowing cell formation. In our experiments, polystyrene films of the thickness of hundreds of micrometers up to a few millimeters were exposed to supercritical CO₂ at saturation conditions in the range of 40-100 °C and 18-28 MPa. Additional experiments were conducted with polystyrene modified with light hydrocarbons. The cell size distribution and porosity of foams were measured and related to the saturation conditions and depressurization time.

The polymer foaming is an interdisciplinary field reaching to polymer rheology, mass transport, thermodynamics, and nucleation. Computational approaches enable insight into foaming phenomena, while experimental techniques are coming that can provide reliable data. Most of theoretical effort is focused on phenomena of cell nucleation and cell growth.¹⁻³ Less attention has been paid to foam vitrification.⁴ As the temperature of CO₂ decreases by its expansion, the polymer in tight contact with growing cells is cooled down until T_g is reached and polymer vitrification occurs. The cell size and foam porosity are fixed at this moment and can be measured after the depressurization is finished. CO₂ solubility in the polymer and T_g depression under the effect of CO₂ play an important role in the process.

While the cell size is related to the solvent solubility in the polymer, in respect to the foam porosity we propose a novel approach considering the changes in the temperature of the mixture in the course of CO₂ expansion due to the Joule-Thomson effect. Heat balance equations including heat transfer over the film surface were integrated to the time when the decreases to T_g. (The necessary properties of CO₂ were available on the NIST web pages and the properties of polystyrene mixtures with CO₂ necessary for the calculations were published in recent research papers.) The estimates were compared with experimental results.

References

1. E. Reverchon and S. Candea, Production of controlled polymeric foams by supercritical CO₂. *J. Supercrit. Fluids* 40 (2007) 144.
2. D.L. Tomasco et al., Development of CO₂ for polymer foam applications. *J. Supercrit. Fluids* 47 (2009) 493.
3. R. Liao et al., Rheological control in foaming polymeric materials: I. Amorphous polymers. *Polymer* 51 (2010) 568.
4. R. Li et al., Glass transition temperature in microcellular foaming process with supercritical carbon dioxide: A review. *Polymer-Plastics Technology and Engineering* 54 (2015) 119.