



národní
úložiště
šedé
literatury

Comparison of Gases Permeation Through Thin Film Composite Membranes.

Morávková, Lenka
2016

Dostupný z <http://www.nusl.cz/ntk/nusl-263113>

Dílo je chráněno podle autorského zákona č. 121/2000 Sb.

Tento dokument byl stažen z Národního úložiště šedé literatury (NUŠL).

Datum stažení: 29.07.2024

Další dokumenty můžete najít prostřednictvím vyhledávacího rozhraní [nusl.cz](http://www.nusl.cz) .

COMPARISON OF GASES PERMEATION THROUGH THIN FILM COMPOSITE MEMBRANES

Morávková L., Kárászová M., Sedláková Z., Vejražka J., Izák P.

*Institute of Chemical Process Fundamentals of the Czech Academy of Sciences, v. v. i.,
Prague, Czech Republic*

The depleting energy sources lead to an intensive search for the equilibrium between economy and environmental sustainability. A biomass belongs to the most promising alternative energy sources. The biomass could be converted into biogas via anaerobic digestion by microorganisms. The biogas generally contains water vapour, 50–65 vol. % of CH₄, 30–40 vol. % of CO₂, traces of hydrogen sulphide, oxygen, nitrogen, ammonia, siloxanes and volatile organic compounds [1]. Removal of CO₂ and other impurities is owing to that heating value of biogas is proportional to CH₄ concentration. Furthermore, these impurities can cause corrosion and freezing problems in pipes and connections. Among all possible alternatives, membrane separations offer a lot of advantages such as energy saving, environmental friendliness, easy handling, continuous process, and small foot prints [2,3].

The membrane separation was studied for various feed composition, feed pressure, temperature in the permeation cell, *etc.* Furthermore, selectivity of the separation was studied with respect to obtaining of pure CO₂. This contribution is focused on comparison of the representative polyamide thin film composite (TFC) membranes for the biogas upgrading.

Application of the TFC membrane separation doesn't require any pre-treatment of the feed gas before the gas separation step compared to the other, e.g. glassy polymer membranes. This fact brings a lot of advantages, for example no lose performance due to plasticization by water vapour. The TFC membranes showed good permselectivity, in case that the feed stream contains at least 85% relative humidity, which condenses onto the membrane surface and guarantees a sufficient humidity of the membrane during the separation process. Moreover, humidity improves the solubility of H₂S and CO₂ in the water sorbed into the TFC membrane in comparison with CH₄.

Acknowledgement

The financial support from the Technology Agency of the Czech Republic (project TE01020080) is gratefully acknowledged.

Literature

1. A.G. Chmielewski, A. Urbaniak, K. Wawryniuk, *Biomass Bioenergy* 300 (2013) 1–10.
2. P. Dolejš, V. Poštulka, Z. Sedláková, J.C. Jansen, P. Izák, *Separation and Purification Technology* 131 (2014) 108–116.
3. M. Kárászová, Z. Sedláková, P. Izák, *Chemical Papers* 69 (10) 1277–1283 (2015).