

INFLUENCE OF IONIC LIQUID CONTENT ON TRANSPORT PROPERTIES OF DENSE POLYMERIC MEMBRANES

Kačírková M.¹, Žitková A.¹, Randová M.², Hovorka Š.², Izák P.¹

¹*Institute of Chemical Process Fundamentals, Rozvojová 135, 165 02 Prague 6, Czech Republic*

²*Institute of Chemical Technology, Technická 5, 160 00 Prague 6, Czech Republic*

Pervaporation was used for the removal of butan 1 ol from its 5 wt. % aqueous solution at which concentration *Clostridium acetobutylicum* fermentation slows down. Two types of membranes were used: a polydimethylsiloxane (PDMS) membrane containing 0, 10, 20 or 30 wt. % of ionic liquid benzyl-3-butylimidazolium tetrafluoroborate ([BBIM][BF₄]) and a polyethylene (PE) membrane in which [BBIM][BF₄] was sandwiched between two PE films. Differential scanning calorimetry measurements showed that PDMS and [BBIM][BF₄] are not compatible and although optically homogeneous, PDMS-[BBIM][BF₄] membranes contained PDMS and [BBIM][BF₄] phases. Pervaporation selectivity increased and the total flux through the membrane moderately raised with the increased content of [BBIM][BF₄] in the PDMS-[BBIM][BF₄] membranes. Hence, the immobilization of a proper ionic liquid in the membrane could be the good method for removal the alcohol from fermentation broths by pervaporation. On the contrary, [BBIM][BF₄] layer sandwiched between two PE films had no practical effect on the pervaporation properties.

Acknowledgement: This research was supported by Ministry of education youth and sports of the Czech Republic (Project COST LD-13018).