



národní
úložiště
šedé
literatury

Removal of PFASs from sewage sludge by pyrolysis

Hušek, Matěj
2022

Dostupný z <http://www.nusl.cz/ntk/nusl-508640>

Dílo je chráněno podle autorského zákona č. 121/2000 Sb.

Tento dokument byl stažen z Národního úložiště šedé literatury (NUŠL).

Datum stažení: 23.06.2024

Další dokumenty můžete najít prostřednictvím vyhledávacího rozhraní nusl.cz .

Removal of PFASs from sewage sludge by pyrolysis

Student: Ing. Matěj Hušek

Supervisor: Doc. Ing. Michael Pohořelý, Ph.D.

Per- and polyfluoroalkyl substances (PFASs) are widely used in industry (packaging, textile, electroplating, metallurgical or plastic industries) because of their valuable properties (low surface tension, nonflammability, hydrophobicity, oleophobicity, or good thermal conductivity).¹ In contrast to properties suitable for industry, PFASs have several adverse health effects (e.g. kidney cancer, sperm quality, or cholesterol level),² and their occurrence in nature is not desirable. The extensive use of PFASs is later reflected in their content in wastewater and subsequently in sewage sludge.³ Thus, agricultural sludge use should be replaced by thermal sludge treatment. Mono-incineration is a well-known technology, in contrast to sludge pyrolysis, which still has some research gaps, especially in the field of the behaviour of organic pollutants, including PFASs.⁴ Our work aimed to describe PFASs behaviour at different pyrolysis temperatures (200 to 700 °C). We analysed 37 PFAS in sewage sludge samples and pyrolysis products. The temperature at which PFASs were removed from the sewage sludge at more than 99.0% was 400 °C, and at 600 °C, removal was more than 99.9%. As a result, it is recommended for commercial sludge pyrolysis units (larger volume, lower material homogeneity) that the process temperature be not lower than 600 °C. This recommendation is supported and demonstrated by the analyses of samples from the Bohuslavice Trutnov WWTP (CZE), where the sludge pyrolysis unit is in operation.

Acknowledgements

This work was supported by the Ministry of Agriculture of the Czech Republic – project QK21020022), Czech Academy of Sciences AV 21 – Sustainable energy, and Specific university research – grant No. A1_FTOP_2022_001 and No. A2_FTOP_2022_003. We also thank our colleagues from UCT Prague and IM CAS, who collaborated on this research.

References

1. Glüge, J.; Scheringer, M.; T. Cousins, I.; C. DeWitt, J.; Goldenman, G.; Herzke, D.; Lohmann, R.; A. Ng, C.; Trier, X.; Wang, Z. An Overview of the Uses of Per- and Polyfluoroalkyl Substances (PFAS). *Environ. Sci. Process. Impacts* **2020**, *22*(12), 2345–2373. <https://doi.org/10.1039/DOEM00291G>.
2. Fenton, S. E.; Ducatman, A.; Boobis, A.; DeWitt, J. C.; Lau, C.; Ng, C.; Smith, J. S.; Roberts, S. M. Per- and Polyfluoroalkyl Substance Toxicity and Human Health Review: Current State of Knowledge and Strategies for Informing Future Research. *Environ. Toxicol. Chem.* **2021**, *40*(3), 606–630. <https://doi.org/10.1002/etc.4890>.
3. Semerád, J.; Hatasová, N.; Grasserová, A.; Černá, T.; Filipová, A.; Hanč, A.; Innemanová, P.; Pivokonský, M.; Cajthaml, T. Screening for 32 Per- and Polyfluoroalkyl Substances (PFAS) Including GenX in Sludges from 43 WWTPs Located in the Czech Republic—Evaluation of Potential Accumulation in Vegetables after Application of Biosolids. *Chemosphere* **2020**, *261*, 128018. <https://doi.org/10.1016/j.chemosphere.2020.128018>.
4. Hušek, M.; Moško, J.; Pohorelý, M. Sewage Sludge Treatment Methods and P-Recovery Possibilities: Current State-of-the-Art. *J. Environ. Manag.* **2022**, *315*, 115090. <https://doi.org/10.1016/j.jenvman.2022.115090>.